
## PISTON TYPE PNEUMATIC OPERATED DIGITAL CONTROL VALVE FT-7883-40P

## **TECHNICAL SPECIFICATION:**

Piston digital control valve works on the principle of "balanced piston" Piston is always exposed to high upstream pressure from its bottom side, whereas pressure in the piston chamber can be varied with the help of solenoid valves. when pressure in the piston chamber is equal to the high upstream pressure, the top spring acts as a differential force, pushing the piston down on the valve seat and the valve is held tightly- closed.



- 1 BASIC VALVE
- 2 NEEDLE VALVE Adj. closing speed
- 3 NEEDLE VALVE Adj. Opening speed
- 4 2-WAY SOLENOID VALVE Normally open
- 5 2-WAY SOLENOID VALVE Normally Closed
- 6 AIR FILTER REGULATOR

VALVE SIZE - INCH	2"	3"	4"	6"
VALVE SIZE - mm	50	80	100	150
F/F (150 ANSI)	238	305	345	508
C/T (Appx.)	175	225	280	365



## FLOW-TEK VALVES & CONTROLS INC

PLOT NO: 172-173, ROAD NO. 4, G.I.D.C., KATHWADA, AHMEDABAD - 382430 (M): 09824080899, 09824539702 PHONE: (079) 22900220, 22900219

E-MAIL: info@flowagevalves.com, hemal21386@gmail.com url: www.delugecontrolvalve.com, www.flowagevalves.com

AN ISO 9001: 2008 CERTIFIED COMPANY